

TABLE TOP CENTRIFUGE DSC-200T

Table Top Centrifuges are widely used in many fields such as biology, medicine, pharmacology, laboratory, and other regions. They are small, compact, strong, easy and safe for operation. The maximum speed is 3000rpm at 60 Hz.

FEATURES:

- The design is up-to-date, presentable look and durable.
- The speed and time are adjustable.
- ABS outer shell can resist collision.
- Brushless, free maintenance.
- Accommodates 2ml~15ml centrifuge tubes without changing the rotor.
- With safety switch, the motor can be stopped when the cover is opened.
- Speed is linear and stable.
- Auto-balancing system.
- Quality Certification: ISO 9001, 13485

ROTORS:











TUBE ADAPTORS:



SPECIFICATION

Model	Max. Speed (RPM)	Timer (Min.)	Speed and RCF Display	Motor	Weight (Kg.) N.G./G.W.	Dimension (mm) (WxDxH)		
DSC-200T	3,000 at 60Hz 2,500 at 50Hz	0~30 min. mechanical timer	Speed and R.C.F. Display	Brushless Induction	3.4 / 4.5	280x280x255		
Power Supply AC 220V 50/60Hz available								

SPECIFICATIONS OF ROTOR

Model	Speed (RPM)	Type	Max. RCF (g)	Capacity	Standard Accessory
AR-1506	300-3000	45° angle	1,066	6x (10~15) ml	(10~15) ml tube adapter
AR-1508	300-3000	45° ang l e	1,066	8x (10~15) ml	(10~15) ml tube adapter



